A tradition of grand performance deserves an encore.

Introducing the Mooney Encore.


The newest Mooney is coming. Fast.

Joining our proud line of high-performance singles in mid-year 1997 is the new 220 hp turbo-intercooled Encore – combining the classic K-model fuselage and the Continental TSIO-360-SB engine.

Outfitted with new-generation propeller technology, the Encore has a projected cruise speed of 200-plus ktas and an IFR range in excess of 800 nm. Maximum gross weight has been significantly improved over previous Mooney models in the same class, providing an additional 200 pounds of useful load.

The airframe is built in the Mooney tradition with a laminar-flow wing built tip-to-tip in one strong, single piece. The cabin is cocooned in a protective roll-bar type frame of chrome-moly steel tubing. Redundant systems provide enhanced safety and reliability as well.

Call today about our new Encore. You'll enjoy the performance.



Projected Performance Data*

Stall speed, landing configuration60 KIASNever exceed speed196 KIABest rate of climb sea level1,300 FBest rate of climb 5,000 ft.1,100 FCruise speed (PWR/SPEED/ALT.)MCP, 21

Maximum range (PILOT, 2 PAX FULL FUEL) Maximum duration

Exterior Dimensions

Span Height Length

Areas

Wing (Sw) Flap (Sf) Ailerons (Sa) Horizontal (Sh) Elevator (Se) Vertical (Sv) Rudder (Sr) Dorsal fin (Sd)

Weights

Empty Gross Useful load Payload (typically equipped) Wing loading Power loading CG range

Cabin Dimensions

Width Height Length Access door Baggage volume

Powerplant Data

Engine SL hp. rating Propeller mfr. Propeller dia. Engine oil capacity Total fuel tank capacity

Landing Gear Data

Wheel track Wheel base Main tires Nose tire 60 кназ 196 кназ 1,300 грм 1,100 грм мср, 210 ктаs, fl250 мср, 213 ктаs, fl220 75%, 197 ктаs, fl220

1,100 NM 6 hrs.

36 ft. 1 in. 8 ft. 4 in. 25 ft. 5 in.

174.786 sq. ft. 17.5 sq. ft. 11.5 sq. ft. 34.42 sq. ft. 13.00 sq. ft. 7.84 sq. ft. 6.23 sq. ft. 1.19 sq. ft.

2000 lbs. 3100 lbs. 1100 lbs. 650 lbs. 17.7 lbs./sq. ft. 14.1 lbs./hp. sta. 41 to 50.1

43.50 in. 44.50 in. 114.0 in. 17.0 x 21.0 in. 13.5 ft.³

TCM TSIO-360-SB 220 * 74.0 in. 8.0 qts. 80 US gal., 78.6 usable

9 ft. 02 in. 5 ft. 11.56 in. 6.00-6 6 ply 5.00-5 6 ply

* All specifications and performance are preliminary and subject to final certification.